

Ronzatori per segnalazioni industriali

Buzzers for industrial applications


V 12-24-48-110-240 ($\pm 10\%$)			50/60 Hz	On ∞
autoestinguente self-extinguishing		IP 30		$^{\circ}\text{C}$ -30 +50



BIP 81
BIP81
①① ②④

V	12	24	48	110	240
V				110	240
mA	3.5	3.5	3.5	3.5	3.5
dB(A)1m	72	72	72	72	72
Hz	1800				

BIP8112DA	42300
BIP8124DA	42301
BIP8148DA	42302
BIP81110D	42303
BIP81110A	42304
BIP81240D	42307
BIP81240A	42308



Kg. 0,04


Installazione ad incasso foro quadro.
Flush mounting with square openings.



BIP 92
BIP92
①① ②④ ③⑥

V	12	24	48	110	240
V				110	240
mA	5	5	5	5	5
dB(A)1m	75	75	75	75	75
Hz	3600				

BIP9212DA	42318
BIP9224DA	42319
BIP9248DA	42320
BIP92110D	42321
BIP92110A	42322
BIP92240D	42325
BIP92240A	42326



Kg. 0,04


Installazione ad incasso foro tondo (\varnothing 16-22-30 mm).
Flush mounting with round openings (\varnothing 16-22-30 mm).



BIP OS 93
BIPOS93
①① ②④ ③⑥

V	12	24	48	110	240
V				110	240
mA	5	5	5	5	5
dB(A)1m	75	75	75	75	75
Hz	4000				

BIPOS9312DA	42336
BIPOS9324DA	42337
BIPOS9348DA	42338
BIPOS93110D	42339
BIPOS93110A	42340
BIPOS93240D	42343
BIPOS93240A	42344



Kg. 0,04

Kg. 0,06


Installazione ad incasso foro tondo (\varnothing 22 mm) o su supporto orientabile.
Flush mounting with round openings (\varnothing 22 mm) or on swivel support.



BIP 84
BIP84
①① ②④ ③⑦

V	12	24	48	110	240
V				110	240
mA	6	6	6	6	6
dB(A)1m	80	80	80	80	80
Hz	2200÷3500				

BIP8412DA	42345
BIP8424DA	42346
BIP8448DA	42347
BIP84110D	42348
BIP84110A	42349
BIP84240D	42352
BIP84240A	42353



Kg. 0,08

Installazione ad incasso foro tondo (\varnothing 30 mm) - doppio LED.
Flush mounting with round openings (\varnothing 30 mm) - double LED.

Per ordinare l'opzione nera vedere codici su listino in vigore. Black option available on request.