



### > SUPERBRIGHT < > NEW RANDOM EFFECT <

Compares to a traditional flashing beacon with a 6 Joules Xenon discharge tube

PC	-30 +50 C°	IP66	ON	CLASS 2	SELF EXTINGUISHING
LED SMD	DIFFUSED	FPM 1F 150 ±/-10 CH 1	CPM 5F 72 ±/-10 CH 2	RANDOM CH 3	3 LEVELS ALARM

### CAN BE INSTALLED WITH



See Base Section on page 28

	SHALLOW		DEEP		WALL	
12/24V ACDC	✓	✓	✓	✓	✓	✓
PNP 12/24V DC	X	X	✓	✓	✓	✓
40/80V ACDC	X	X	✓	✓	✓	✓
120/240V AC	X	X	✓	✓	✓	✓
JR 120/240V AC	X	X	✓	X	✓	✓
	FLUSH		DOUBLE		POLE	

### CERTIFICATIONS



### SLR S | PART NO

allCOLOR	90851	90852	90853	90854	90856
allCLEAR	90861	90862	90863	90864	-

## SLR S new

Multifunctional LED beacon with high optical performance. Developed with a multichannel technology, SLR S allows three separate light effects (flashing, strobe, random) controllable via independent electric contacts.

Available with allCOLOR and allCLEAR lens, SLR S is the right choice for a high-end LED flashing beacon.

### TECHNICAL SPECIFICATIONS

#### MULTIFUNCTION

3 separate functions (flashing, strobe, random) controllable via independent electric contacts

#### HIGH OPTICAL PERFORMANCE

##### CHANNEL 1 | FLASHING LIGHT

Powerful flashing effect ideal for attracting attention yet without alarming

##### CHANNEL 2 | STROBE LIGHT

A 5x strobe effect ideal for all applications where an immediate attention gain is mandatory

##### CHANNEL 3 | RANDOM LIGHT

A unique random effect consisting in an uneven flashing pattern, augmenting the ability of catching attention

#### VOLTAGES

According to the installed base

#### PROTECTION GRADE

IP66, UL TYPE 4X (pending), suitable for outdoor applications

#### OPERATING TEMPERATURE

-30/+50 °C

#### LED TECHNOLOGY

Virtually zero maintenance thanks to the built-in LED technology that guarantees up to 100.000\* hours of product life

\* At normal conditions, without vibrations and heavy temperature changes

### MECHANICAL FEATURES

Self extinguishing PC body with high impact resistance, suitable for outdoor applications thanks to the IP66 protection grade

### OPTICAL FEATURES

2x SuperBright LEDs with inner Fresnel lens. Available with 2 different lens types, according to the final application

#### allCOLOR STANDARD USE

Colored lens with colored light source. The use of a colored lens with the same-color light source allows optimization of the emission frequency producing a rich intense light output

#### allCLEAR USE IN VERY BRIGHT ENVIRONMENTS

Clear lens with colored light source. In very bright environments it is possible that the ambient brightness lights up the device when it is switched OFF creating problems in distinguishing between the ON and OFF state of the device (phantom effect). The clear lens allows clear distinction between the ON and OFF status of the device

### DRAWINGS, DIMENSIONS AND WEIGHTS

