



All you need in an MDI Meter

Introducing the D3 MDI Rev1



Features

- Displays all 3 phases in 1 instrument
- Reliable bright LED display for both high and low ambient light levels
- Displays Amp Demand, Maximum Amp Demand, Instantaneous Current and Voltage per phase
- Easy to set up, saves on space and wiring time
- Standard 96x96 size
- Set Up on front display

Specifications

- Measured Parameters; Voltage, Instantaneous Current, Current Demands.
- Selectable Demand Period; 2-60Min intervals
- Display; 3 rows of bright LEDs 14mm high
- Accuracy; +/- 10%
- Rated Input Voltage; 50V – 500V
- Rated Input Current; 5A or 1A Programmable
- Frequency; 45-65Hz
- Aux Supply; 230VAC *Option 80-265VAC/DC
- Burden; 0.2VA max per phase. 2VA on auxiliary supply.
- Temperature; Ambient -10 deg C to 55 deg C - Storage -10 deg C to 70 deg C
- Relative Humidity; Less than 95%.Non condensing.

CARREL-ELECTRADE LIMITED

Auckland Tel: 09-525 1753
Fax: 09-525 1756

Christchurch Tel: 03-366 1242
Fax: 03-379 1991

Email: sales@carrel-electrade.co.nz
Web: www.carrel-electrade.co.nz