



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SESALR		
MATERIAL		HOUSING-AL LENS-TEMPERED CLASS REFLECTOR-PC		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.		120 ~ 140		
USE VOLT.	LED	CURRENT	1W	MAX. 2.633A MAX. 1.288A MAX. 0.308A MAX. 0.154A
VOLUME		MAX. 118dB		
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" NPT		
COLOR OF HOUSING		MUNSELL NO.7.5BG 7/2		
ACTION		LED REVOLVING WARNING LIGHT		

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓢ	v	
0.5~3	±0.05	±0.1	±0.2	-	
3~6			±0.3	±0.5	
6~30	±0.1	±0.2	±0.5	±1	
30~120	±0.15	±0.3	±0.8	±1.5	
120~400	±0.2	±0.5	±1.2	±2.5	
400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°	
	10~50	±0°30'	±1°	±2°	
	50~120	±0°20'	±0°30'	±1°	
	120~400	±0°10'	±0°13'	±0°30'	

SURFACE FINISH		-		1		
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			MODEL			
SESALR OUTLINE DRAWING			SESALR			
			DWG. NO.		SESALR_OUT	
			SCALE	SIZE	REV	SHEET
N/S	A4	00	1/1			