



AVVISATORI ACUSTICO/LUMINOSI INDUSTRIALI

DOUBLE WARNING SIGNALS – AUDIBLE/VISUAL / DISPOSITIFS DE SIGNALISATION ACOUSTIQUE/LUMINEUSE / INDUSTRIE-SIGNALHUPEN MIT WARNLICHT / DISPOSITIVOS DE SEÑALIZACIÓN ACÚSTICO/LUMINOSA

V 12 -24 -48 -110 -240 (±10%)	==	~ 50/60 Hz	Ba 15d -5w -10w LD	105 115 145 F	IP 43	
On ∞	Hz (==) 650±50	Hz (~) 300÷7000		°C -30 +50		

AUTOESTINGUENTE SELF-EXTINGUISHING AUTO-EXTINGUIBLE SELBSTLÖSCHEND AUTOEXTINGUIBLE		1	2	3	4	5	6	PC
--	--	----------	----------	----------	----------	----------	----------	----

	V ==	12 ÷ 24 ÷ 48		
		mA	480	250
BA 15d 5W LR BA 15d 5W	Cd (p)	4	3	3
		mA	880	470
BA 15d 10W LR BA 15d 10W	Cd (p)	6	5	5
		dB(A)	96	96
Hz		650 ± 50		

	V ~	24 ÷ 48 ÷ 110 ÷ 240			
		mA	350	210	100
BA 15d 5W LR BA 15d 5W	Cd (p)	4	3	3	3
		mA	600	330	150
BA 15d 10W LR BA 15d 10W	Cd (p)	5	5	4	4
		dB(A)	92	92	92
Hz		300 ÷ 7000			




Flash/min. 110±20

LUCE LAMPEGGIANTE - SUONO CONTINUO
FLASHING LIGHT – CONTINUOUS SOUND
LUMIERE CLIGNOTANTE – SON CONTINU
BLINKLICHT – DAUERE TONFOLGE
LUZ INTERMITENTE – SONIDO CONTINUO

SLEM L
SLEML

12

SLEML12D2	40322	SLEML24A2	40642	SLEML48A2	40372	SLEML240A2	40702
SLEML12D3	40323	SLEML24A3	40353	SLEML48A3	40373	SLEML240A3	40423
SLEML12D4	40324	SLEML24A4	40354	SLEML48A4	40374	SLEML240A4	40424
SLEML24D2	40342	SLEML48D2	40362	SLEML110A2	40392		
SLEML24D3	40343	SLEML48D3	40363	SLEML110A3	40393		
SLEML24D4	40344	SLEML48D4	40364	SLEML110A4	40394		



	V ==	12 24 48 110 240				
		mA	480	250	130	55
BA 15d 5W LR BA 15d 5W	Cd (p)	4	3	3	2.5	2.5
		mA	880	470	250	115
BA 15d 10W LR BA 15d 10W	Cd (p)	6	5	5	4	4
		dB(A)	96	96	96	96
Hz		650 ± 50				

	V ~	12 24 48 110 240				
		mA	550	350	210	100
BA 15d 5W LR BA 15d 5W	Cd (p)	4	3	3	2.5	2.5
		A	1	0.6	0.33	0.15
BA 15d 10W LR BA 15d 10W	Cd (p)	6	5	5	4	4
		dB(A)	92	92	92	92
Hz		300 ÷ 7000				




LUCE FISSA - SUONO CONTINUO
CONTINUOUS LIGHT – CONTINUOUS SOUND / LUMIERE FIXE – SON CONTINU
DAUERLICHT – DAUERE TONFOLGE / LUZ FIJA – SONIDO CONTINUO

SLEM F
SLEMF

12

SLEMF12D2	40622	SLEMF24A1	40711	SLEMF48A4	40674	SLEMF240D4	40414
SLEMF12D3	40623	SLEMF24A2	40712	SLEMF110D2	40682	SLEMF240A1	40721
SLEMF12D4	40624	SLEMF24A3	40713	SLEMF110D3	40683	SLEMF240A2	40422
SLEMF12A2	40632	SLEMF24A4	40714	SLEMF110D4	40684	SLEMF240A3	40703
SLEMF12A3	40633	SLEMF48D2	40662	SLEMF110A2	40692	SLEMF240A4	40704
SLEMF12A4	40634	SLEMF48D3	40663	SLEMF110A3	40693	SLEMF240A5	40705
SLEMF24D2	40352	SLEMF48D4	40664	SLEMF110A4	40694	SLEMF240A6	40706
SLEMF24D3	40643	SLEMF48A2	40672	SLEMF240D2	40412		
SLEMF24D4	40644	SLEMF48A3	40673	SLEMF240D3	40413		



V 24 -110 -240 (±10%)	==	~ 50/60 Hz	J 2	2 F	Flash/min. 65±10
IP 43	On ∞	Hz (==) 650±50	Hz (~) 300÷7000		°C -30 +40

AUTOESTINGUENTE SELF-EXTINGUISHING AUTO-EXTINGUIBLE SELBSTLÖSCHEND AUTOEXTINGUIBLE		1	2	3	4	5	6	PC
--	--	----------	----------	----------	----------	----------	----------	----

LUCE A FLASH - SUONO CONTINUO
XENON FLASHING LIGHT – CONTINUOUS SOUND / LUMIERE A ECLATS – SON CONTINU
BLITZLICHT – DAUERE TONFOLGE / LUZ DE DESTELLOS – SONIDO CONTINUO




SLEM X
SLEM X

12

	V ==	24
		mA
	Cd (p)	200
		100
	dB(A) 1m	96
Hz	650±50	

	V ~	24 110 240		
		mA	500	80
XENON 2J LRX 2J	Cd (p)	200	75	120
		100	35	90
dB(A) 1m	92	92	92	
Hz		300÷7000		



SLEM X24D2	40432	SLEM X110A2	40452
SLEM X24D3	40433	SLEM X110A3	40453
SLEM X24D4	40434	SLEM X110A4	40454
SLEM X24A2	40442	SLEM X240A2	40462
SLEM X24A3	40443	SLEM X240A3	40463
SLEM X24A4	40444	SLEM X240A4	40464