



ALL NEW LED TOWER LIGHTS

The TOWER SECTOR LIGHTS SYSTEM was designed with simplicity and ease of use in mind, it was given a modular construction. This means there are no tools required to assemble TOWER SECTOR. Electrical wiring between the light modules and base is automatic and complete. The securing ring has a tooth locking feature that keeps the unit tight when subject to vibration. Each light module plugs right on top of each other. Simply insert the light module tab and twist the lock ring. That's it!



Voltages

24VAC/DC or 240VAC

SOUNDER UNITS ALSO AVAILABLE

FIVE COLOURS TO CHOOSE
FROM. ALL AT THE SAME
PRICE.

ASK FOR THE TWSSMD-M
TOWER LIGHTS TODAY!!!!



ONE SECTOR CAN DO

4 DIFFERENT LIGHT FUNCTIONS STATIC,
SINGLE FLASH, DOUBLE FLASH AND
TRIPLE FLASH

ALL DIP SWITCH SELECTABLE

TECNOLOGY

12 LATEST GENERATION LED SMD

120 deg Angle Light Emission

72mm modules

IP65

PTO.
PART NO.



TWSSMD-M SERIES PART NUMBERS

TWSSMD-M-24/AM SMD LED TOWER SECTOR MULTI 24VAC/DC AMBER

TWSSMD-M-24/BL SMD LED TOWER SECTOR MULTI 24VAC/DC BLUE

TWSSMD-M-24/CL SMD LED TOWER SECTOR MULTI 24VAC/DC CLEAR

TWSSMD-M-24/GR SMD LED TOWER SECTOR MULTI 24VAC/DC GREEN

TWSSMD-M-24/RD SMD LED TOWER SECTOR MULTI 24VAC/DC RED

TWSSMD-M-24/YE SMD LED TOWER SECTOR MULTI 24VAC/DC YELLOW

TWSSMD-M-240/AM SMD LED TOWER SECTOR MULTI 240VAC AMBER

TWSSMD-M-240/BL SMD LED TOWER SECTOR MULTI 240VAC BLUE

TWSSMD-M-240/CL SMD LED TOWER SECTOR MULTI 240VAC CLEAR

TWSSMD-M-240/GR SMD LED TOWER SECTOR MULTI 240VAC GREEN

TWSSMD-M-240/RD SMD LED TOWER SECTOR MULTI 240VAC RED

TWSSMD-M-240/YE SMD LED TOWER SECTOR MULTI 240VAC YELLOW

Accessories: TWS

**Sounder units also available AC/DC,
6 sounds, 86dB - 78dB, IP54 - IP65**



TWS PR

100mm Extension Stem



TWS BS

Mounting Base



TWS BP1

Single Wall Mounting



TWS BOX PG9



TWS AFF

OVOLD coupling
(for TWS BS)



TWS BP2

Double Wall Mounting



TWS KIT

100mm Pole Mounting



TWS BC

Wiring Base & Cover