

SOLITRONICS ENGINEERING LTD.

2202, Perfect Industrial Bldg. 31, Tai Yau St. San Po Kong Kowloon Hong Kong

TEL : (852) 2730-8145 FAX : (852) 2730-3245 E-mail : info@solitronics.com

Ø16mm Panel Mount Buzzer

Group: Part Number: Data She


SE-16D SE-16D-BZ-FX-XX-X


IEC-60947 GB-14048.5

Data Sheet:

SE-16D-BZ

13th Nov. 2009













Drilling Plan for Form-1

Drilling Plan for Form-2&3

18x24mm Form 1

18x18mm Form 2

Φ18mm Form 3

Product	Style	Туре	Voltage	Sound Type	Rated Volume and Frequency	Outline Dimensions (mm)
18x24mm Buzzer	Form-1	SE-16D-BZ-F1	21=6V AC/DC 22=12V AC/DC 23=24V AC/DC 24=36V AC/DC 25=48V AC/DC	A=Intermittent (5-pips per second followed by 1-second interval) B=Continuous	80dB at a distance of 10cm at rated voltage 2300Hz ± 400Hz	minal 2.8 · 0.5) (Thickpreps) - 6
18x18mm Buzzer	Form-2	SE-16D-BZ-F2				Square Top View Round Top View
18mmØ Buzzer	Form-3	SE-16D-BZ-F3				Rectangular Top View

Ordering Code: SE-16D-BZ-FX-XX-X

Remarks:

As of 1st of Jan. 2008, the 2.8mm solder-terminals are now changed to "Direct PCB terminal for soldering"

Note: Due to continuous development, all specifications and availability are subject to change without prior notice. Please confirm all details at time of ordering.